



NOTES

1. PROVIDE INFANT THEFT SECURITY SYSTEM AS REQUIRED BY USING MILITARY DEPARTMENT.
2. EITHER PLATE 4.02.02 OR 4.02.03 MAY BE USED FOR A LDR OR LDRP. VERIFY WITH USER.

KEY NOTES

1. MOUNT 1-AS145, HOOK, AT 1372 [4'-6"] AFF AND 1-AS145 AT 1524 [5'-0"] AFF.
2. PROVIDE AS030, BENCH, FOR NAVY PROJECTS. TERMINATE AS110, GRAB BAR, ABOVE BENCH LOCATION.
3. PROVIDE AS109 AND AS110, GRAB BARS, THAT COMPLY WITH ADA.
4. BASEBOARD RADIATOR MAY OCCUR AT EXTERIOR WALL.
5. SEE ELEVATIONS OF F0550, RESUSCITATION ARMCHAIR, AND A1110, HEADWALL, FOR UTILITIES.
6. P3200, UTR ELECTRONIC LAVATORY, MAY BE USED INSTEAD OF P3100, LAVATORY. FOR THE P3200 PROVIDE EITHER BATTERY POWER OR HARD WIRED CONNECTION.
7. COORDINATE LOCATION OF ELECTRICAL OUTLETS WITH M1802, WALL MOUNTED, FOLD DOWN COMPUTER.
8. WHERE FEASIBLE, SLOPE TOILET ROOM FLOOR TOWARDS THE SHOWER.
9. MOUNT 1-AS185, SHELF, AT 1219 [4'-0"] AFF AND 1-AS185 AT 1524 [5'-0"] AFF.
10. MOUNT AS145, HOOK, AT 1219 [4'-0"] AFF.
11. PROVIDE M7445, SURGICAL LIGHT, INSTEAD OF M7515, SURGICAL LIGHT, FOR AIR FORCE PROJECTS. LIGHT REQUIRES BATTERY BACKUP OR UPS.

L & D - LDR/LDRP (Narrow)
& TOILET, SHOWER, INPATIENT (LDRP1/TLTS2)

LABOR & DELIVERY/OB UNIT	0	1000	2000
FLOOR/EQUIPMENT PLAN	45.45 NSM (489 NSF)		
DATE: 07/12/2001		1:50 SCALE (MILLIMETERS)	